



■ Made
■ in
■ Germany



Softsynchro®

EMUGE

Montagevorrichtung mit wechselbaren Adapterplatten
Assembly Device with Changeable Adapter Plates

Basis-Montagevorrichtung
Basis assembly device

Softsynchro®



Für Spannzangen-Aufnahmen
For collet holders

Artikel-Nr.
Article no.

Softsynchro® Micro, Softsynchro® 0, Softsynchro® 1, Softsynchro® 3, Softsynchro® 4

F3151186



Adapterplatten
Adapter plates

Softsynchro®

Softsynchro® Micro



Softsynchro® 0



Softsynchro® 1



Softsynchro® 3



Softsynchro® 4



Für Spannzangen-Aufnahmen
For collet holders

Empfohlenes Anzugsdrehmoment ¹⁾
Recommended tightening torque ¹⁾

Schlüsselweite
Width across flats

SW

Artikel-Nr.
Article no.

Softsynchro® Micro	6 Nm	8 mm	F315050.02	●
Softsynchro® 0	12 Nm	14 mm	F315050.03	●
Softsynchro® 1	32 Nm	19 mm	F315150.01	●
Softsynchro® 3	90 Nm	32 mm	F315350.01	●
Softsynchro® 4	180 Nm	41 mm	F315450.01	●

¹⁾ Anzugsdrehmoment gilt für Spannmutter Typ Hi-Q/ERC
Tightening torque is valid for the clamping nut type Hi-Q/ERC